



C(D)RB2*W10~40-Z, Rotary Actuator, New Vane Style CDRB2BWU40-180SZ

Datasheet

General series information

- Standard type.
- Piping ports are located on the flat surface.
- Many variations of shaft-end shape (6 types).

Standard specifications

| | |
|--|---|
| Magnet | D (Built-in) |
| Mounting | B (Basic) |
| Standard Shaft Type | W (Double Shaft with Single Flat) |
| Angle Adjusting Unit | U (Angle Adjuster) |
| Size | 40 mm |
| Rotation Angle - Vane | 180S (Angle: 180 Single Vane) |
| Port | Side |
| Auto Switch | No Switch |
| Lead Wire or Prewired Connector | 0.5m (Or None in the Case of No Switch) |
| Number | 2 pcs. (Or None in the Case of No Switch) |
| Pressure medium | Air (Non-lube) |
| Maximum temperature of pressure medium | 60 °C |
| Minimum temperature of pressure medium | 5 °C |
| Maximum ambient temperature | 60 °C |
| Minimum ambient temperature | 5 °C |
| Number of pneumatic connections | 2 pcs. |
| Geometric form of the piston rod | Single rod |

Additional information

Catalogue

[CRB2-C_EU.pdf](#)

Operation manuals

[OM_CRB2_OM00001EN-B.pdf](#)